



# Global Full Synthetic Multi-Vehicle ATF

DuraMAX Global Full Synthetic Multi-Vehicle ATF is formulated for the newest generation of high efficiency transmissions and is also a fuel efficient choice for older models.

CATEGORY	TEST METHOD	TYPICAL VALUE
Gravity, °API	ASTM D287	35.6
Specific Gravity @ 60°F (15.6°C)	ASTM D4052	0.8468
Viscosity @ 40°C cSt	ASTM D445	28.56
Viscosity @ 100°C cSt	ASTM D445	5.797
Viscosity Index	ASTM D2270	151
Pour Point °C (°F)	ASTM D5950	-51 (-60)
Brookfield Viscosity at -40°C, cP	ASTM D2893	10,300
Color	ASTM D1500	Red



DuraMAX Global Full Synthetic Multi-Vehicle ATF is DEXRON® VI approved and suitable for use in the following applications:

- » Type A
- » Allison C-4
- » Allison TES-389
- » Dexron® VI
- » GMN10060
- » Audi G 052 025, 052 162, 055 025
- » Esso 71141
- » BMW P/N 83 22 0 024 359, ETL-8072B
- » BMW P/N 83 22 0 0246 922, ETL-7045E
- » BMW P/N 83 22 0 403 249, ETL-8072B
- » BMW P/N 83 22 9 407 765, LA 2634
- » BMW P/N 83 22 9 407 807, LT 711 41
- » Dexron III G/H, Dexron II, Dexron, AW1
- » Honda DW-1, Z-1
- » Volvo P/N 1161540-8
- » Hyundai/Kia/Mitsubishi Diamond SP-II, RED-1, SP-IV
- » Chrysler AS68RC, Diamond SP-III
- » Chrysler P/N 05127382AA, P/N 68043742AA (DEX VI)
- » JWS 3309, Any 3309
- » M315-2004 JASO 1A, 2A
- » MAN 339 Type Z1, Z2, V1
- » MAN 339 Type V2
- » Mazda ATF M-III, MV, T-IV
- » NAG-1
- » MB 223.2, 236.1, 236.2, 236.10, 236.12, 236.41, 236.5, 236.6, 236.7, 236.8, 236.9
- » Shell M-1375.4
- » Mercon V (XT-5-QM, XT-5-DM)
- » Mercon, Ford ESP-M2C166-H
- » Mercon SP, except 6HP26 / 6R60 / 6R75 transmissions
- » XT-6-QSP, XT-6-DSP, except 6HP26 / 6R60 / 6R75 transmissions
- » Mercon LV (XT-10-QLV)
- » Nissan Matic-D, J, K, 402
- » Texaco N402
- » Nissan Matic, J, S
- » Shell 3403, LA2634, Texaco 7045-E, ETL-8072B
- » Hyundai NSWS9638
- » Fuchs 3353
- » IDEMITSU APOROIL ATF HP
- » ISUZU 08200-9001 / Genuine ATF
- » MINI P/N 83 22 0 402 413
- » Saturn P/N 21005966
- » SAAB P/N 22 717 466, 93 165 147 (AW-1)
- » Jaguar P/N WSS-M2C922-A-1
- » Porsche P/N 999 917 547 00 (A2)
- » VW P/N GUS 000 162
- » Shell 3403 M115
- » Subaru ATF, ATF-HP
- » Toyota T-II, T-III, T-IV, WS, Ford XT8QAW
- » Saturn T-IV, GM TASA, T-IV ATF, GM WS ATF
- » JWS 3324
- » Voith 55.6335 (G607)
- » Volvo Passenger Car (4-6 sp), Volvo 97340, 97341
- » VW G 052 025, 162, 099, 055 025
- » ZF TE-ML 02F, TE-ML 03D, TE-ML 04D, TE-ML 09, TE-ML 11A
- » ZF TE-ML 14A, TE-ML 14B, TE-ML 14C, TE-ML 16L, ZF TE-ML 17C
- » VW TL52162 (LT71141)

[www.RelaDyne.com](http://www.RelaDyne.com)

WD.N6LVPL.031616

Always confirm that the product selected is consistent with the original equipment manufacturer's recommendation for the equipment operating conditions and customer's maintenance practices.

©2016 RelaNyne® | 9395 Kenwood Road, Suite 104 Blue Ash, OH 45242 | [www.RelaDyne.com](http://www.RelaDyne.com)

